

PERSONAL AIR SAMPLER & RADIATION ALARM

Model # MINI-AIR RAD Total Airborne Activity


Model# MINI-AIR Sampler for all Airborne Hazards

FEATURES:

- NEW REALTIME FLOW METER
- VARIABLE RATE 1-3 Lpm.
- DETECTS 6×10^{-8} $\mu\text{Ci/cc}$ in 30 minutes
- BATTERY OPERATED
- INTEGRATED EXPOSURE
- READS DIRECTLY IN Cts/Sec or μCi
- CAN DRAW AIR FROM ROOM OR BREATHING ZONE
- QUICK CHANGE FILTER
- OPTIONAL SNIFFER HOSE
- OPTIONAL: RS-232 COMPUTER AND/OR DATALOGGER INTERFACE

APPLICATION: The Mini-Air Series Air Monitor assures Safety against airborne radioactivity contamination by means of constant monitoring check. Optional alarm and record capability. It provides integrated exposure information. The MINI-AIR Series is sensitive and versatile. Although designed as an industrial workplace and hospital breathing air measurement system, it may also be used to monitor fume hoods and stack effluent.

DESCRIPTION: The MINI-AIR Series uses standard or charcoal filters in TA's unique quick change, no leak holders to trap any airborne radio-nuclides. The filter is under constant surveillance via a GM detector. Air is drawn by a high volume pump through the filter and exhausted to the room or through an optional hose. An Inlet and outlet hose may be attached to allow monitoring of hoods, glove boxes, stacks, etc. Time is controlled by a rocker switch wired into the pump circuit. The unit is completely self-contained and portable. Complete with 10 charcoal and 100 glass fiber filter disks.



MINI-AIR-RAD



TBM-3D

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE (818) 883-7043 • FAX (818) 883-6103
e-mail: tagold@nwc.net • www.tech-associates.com

PERSONAL AIR SAMPLER & RADIATION ALARM

Model # MINI-AIR RAD Total Airborne Activity

Model# MINI-AIR Sampler for all Airborne Hazards

SPECIFICATIONS:

- Electronics:** TBM-3D Programable Digital Ratemeter
- Pump:** Miniature 1-3 Liter/min Pump and Filter holder.
- Power:** Standard 9V (and (6) AA Batteries in TBM-3D) Rechargeable batteries ok.
- Range:** 1×10^{-10} to 1×10^{-5} μ Ci/cc (or Ci/m³) (Depends on count time)
- Readout:** 6 Digit LCD - TBM-3D.
- Flow meters:** Displays flow rate 1.0 – 3.0 Lpm.
- Adjustable Flow Rate:** variable from 1 to 3 Lpm
- Filters:** Includes package of 100 glass Fiber and 10 charcoal filter papers. (Can also use membrane filters.)
- Case:** Electronics housed in enameled aluminum housing; handle included.
- Dimensions: Air Sampler Dimensions**
Including pump and detector assembly: 1.75" diameter x 8.5" Long.
Including Scaler TBM-3D; 3" W x 4" L x 5.5" H excluding handle.
- Shipping Weight:** 6 lbs.
- Options:**
A variety of sensitive detectors for non-radiation hazards such as Smoke & Fumes from Diesel or Cigarettes, as well as Biological and Chemical Threats and Toxins.- Call for Details

Easy Procedure for Use:

Flow-rate has been preset (user can change those if desired).

1. Turn on Ratemeter or Scaler.
2. Put in clean filter.
3. Make Test Count (pump Off).
4. Detach sampler and clip it to your belt.
5. Turn on Pump.
6. At end of job or workshift, Reattach Ratemeter.
7. Digital display reads out directly in counts per second, or in uCi trapped in the filter (for a single isotope of interest with known conversion factor).
 - A. Filter must be clean at start of each new air sample.
 - B. User can change scale factor in order to readout in different units.

Optional use of rechargeable batteries:

When rechargeable batteries are used place low charge batteries into an external charger.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE (818) 883-7043 • FAX (818) 883-6103
e-mail: tagold@nwc.net • www.tech-associates.com

PERSONAL AIR SAMPLER & RADIATION ALARM

Model # MINI-AIR RAD Total Airborne Activity

Model# MINI-AIR Sampler for all Airborne Hazards

MODEL:	MINI-AIR-RAD	MINI-AIR
Has Belt Clip:	Yes	Yes
Detector:	T-1210 GM Tube	External
Size/Material:	1` dia. Pancake	
Window:	Mica 1.5 - 2.0 mg/cm ²	
Detector: Radiation	Alpha, Beta, Gamma	STB-3 (External)
Biological Hazards; Chemical Hazards	Optional Optional	Optional Optional
Iodine:	Optional	Optional
Detects Particulates:	Yes	Yes
Detects Aerosol & Reactive Gases*:	Yes	Yes
Filter: Glass Fiber Charcoal Filter Paper- 1" dia	Yes Optional	Yes Optional
Iodine Sensitivity: (30 min)	5 x 10 ⁻⁸ µCi/cc	
Public Release: (1 x 10⁻¹⁰ µCi/cc)	10 Hour exposure	
Weights:		
Electronics:	2 lbs	See Choices
Detector + Filter Holder:	1 lbs	1 lbs
Pump:	Included	Included
RAD Shielding:	Optional	None
*Detects all airborne activity except H-3,Fe-55 and Noble Gases,	Yes	N/A
Electronics:	TBM-3D	See Options

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE (818) 883-7043 · FAX (818) 883-6103
e-mail: tagold@nwc.net · www.tech-associates.com