

PORTABLE RADON MONITOR Model # TBM-IC-RN

FEATURES:

- DIGITAL READOUT:
6 Digits Rate,
8 Digits Integrate
- SMALL LIGHTWEIGHT 26 oz.
- TBM PACKAGE
- FLAT RESPONSE - FREE AIR ION CHAMBER
- SEES AXIALLY BELOW 5 KEV GAMMA OR X-RAY
- FAST RESPONSE
- WIDE RANGE



APPLICATION:

Whenever a fast, sensitive Radon Detector is needed, the **TBM-IC-RN** detects 10 picoCi/l in 5 seconds and detects public release level in less than 10 minutes. This instrument is the latest in a series. The **TBM-IC-RN** ion chambers are now smaller and lighter and based on newest stable, essentially drift-free electrometer technology.

DESCRIPTION: The **TBM-IC-RN** consists of a 2.9" dia x 3.5" long air ion chamber coupled to a stable solid state MOSFET input electrometer with built in A to D converter to read out directly in a nanoCi/liter. Range is 10 picoCi/l to 1 μ Ci/l. Ion Chamber walls are 180 mg/cm² graphite lined methacrylate walls and give accurate "air equivalence." Quick change Ion Chamber Shell allows conversion to TBM-IC-Survey Meter.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE (818) 883-7043 · FAX (818) 883-6103
e-mail: tagold@nwc.net · www.tech-associates.com

PORTABLE RADON MONITOR Model # TBM-IC-RN

SPECIFICATIONS:

- Detector:** Free Air ion chamber 2.9" dia x 3.5" long. Internal volume 300 cc.
- Wall & Cap:** Methacrylate, graphite lined 180 mg/cm² walls and 540 mg/cm² cap.
- Readout:** LCD: 6 Digits Rate; 8 Digits Integrate.
- Indicator Lamp:**
 - Green LED 10 pulses/sec per mR/h.
 - Red Over-range Indicator.
- Range:**
 - Rate** 6 digit 10 picoCi/liter to 1 µCi/liter in a single range.
 - Integrate** 8 digits 1 picoCi/liter* to 100,000 pCi/liter in a single range.
*less than 1 minute Indicator.
- Note:** TBM-IC-RN in Integrate Mode has no timer. User must provide clock or stopwatch.
- Electrometer:** Solid State MOSFET input.
- Electronics:** A-D converter LCD drivers.
- Batteries:**
 - 10 ea. (Button) NEDA CR-1220 - shelf life 7 years.
 - 6 ea. (AA) NEDA 15A – 1000 hr.
- Dimensions:** 11" x 4" x 8" including handle and optional pump.
- Air Flow:** Passive Diffusion or lightweight Battery powered pump.
- Weight:** 26 oz. complete with batteries. **Optional** pump is 2 lbs.
- Options:** Readout in Si units: KBq/m³.
- Optional**
- Pump:** Flow Rate: 4 SCFH. Batteries: 2 AA Batteries.

Working Level and Rn-222 Radon Gas vs. Radon Daughters:

Option 1: Particulate pre-filter removes much of the Radon daughters from the in-coming air stream but lets the Radon gas pass into the ion chamber for measurement.

Option 2: Activated charcoal pre-filter which stops much of the Radon gas is also available.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE (818) 883-7043 · FAX (818) 883-6103
e-mail: tagold@nwc.net · www.tech-associates.com