

HIGH VOLTAGE TESTER

高压测试器

**DIGITAL D.C.
Model # HV 2000**

FEATURES: 特点

- 3 1/2 DIGIT DISPLAY
- 3 1/2 数字显示
- DIRECT MEASUREMENT OF H.V. 0-2000 V DC
- 直接测量高压 0-2000 V DC
-
- HI IMPEDANCE INPUT - 1100 MEGOHM LESS THAN 1 μ A DRAIN AT 1000V
- 高阻输入-1100 兆欧姆, 1000v 时输出电流小于 1 μ A
- 9 VOLT BATTERY OPERATION
- 9v 电池操作
- SHIRT POCKET SIZE
- 口袋尺寸
- LIGHTWEIGHT
- 轻量



HV-2000

DESCRIPTION: D.C. High voltage measurements no longer require large expensive probe and no longer tie up oscilloscope or multimeter.

This small light-weight H.V. tester gives accurate digital readings. Its 1100 megohm input resistance prevents tester from loading down the circuit being tested.

Ideal for use in test and calibration of power supplies used in televisions, lasers and radiation monitors.

描述: D.C.高压测量无需大而贵探头, 无需绑定示波器或多功能表。

这款小而轻量的高压测试器给出精确数字读数。1100 欧姆输入电阻防止被测电路耗电过多



TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

Divisions of  US NUCLEAR CORP

HIGH VOLTAGE TESTER

高压测试器

DIGITAL D.C.
Model # HV 2000

SPECIFICATIONS: 规格

- **Display:** 3 1/2 digits, 1/2" high, LCD.
- **显示:** 3 1/2 数显, 1/2" 高, LCD.
- **Ranges:** 0-1000 Volts and 0-2000 Volts.
- **量程:** 0-1000 V 和 0-2000 V
- **Input Impedance:** 1100 megohm.
- **输入阻抗:** 1100 兆欧
- **Readable:** To one Volt on 0-1000 range.
- **可读出:** 在 0-1000 量程内可读出 1V
- **Accuracy:** Two volts on 0-2000V range 1% plus 1 digit.
- **精度:** 0-2000V 内为±2V, 1% 时加 1 位数
- **Power:** Standard 9 Volt transistor battery.
- **电源:** 标准 9v 晶体电池
- **Battery Life:** 200 hours.
- **电池寿命:** 200 小时
- **Size:** 2-3/4" wide x 5 1/2" long x 1-1/8" thick.
- **尺寸:** 2-3/4" 宽 x 5 1/2" 长 x 1-1/8" 厚
- **Weight:** Less than 5 1/2 oz. including battery.
- **重量:** 小于 5 1/2 oz. 包括电池
- **Material:** Case is made of rugged PVC.
- **Controls:** 控制
 - **Power Switch:** On-Off.
 - **电源开关:**
 - **Range Switch:** x1 (0-999V), x2 (0-1999V).
 - **量程开关:** x1 (0-999V), x2 (0-1999V).
 - **Calibration Pot:** 20 turn precision potentiometers.
 - **定标电位计:** 20 转精确电位计
- **Calibration:** Each unit supplied with calibration certificate.
- **校准:** 每台带校准证书
- **Input:** BNC/MHV connector bulkhead F.
- **输入:** BNC/MHV bulkhead F 接头
- **Cable:** BNC to BNC M cable furnished. BNC to Dual "meatball" style protected clip leads (Model 3787C36) **Optional.**
- **缆线:** BNC 对 BNC M 缆线, 可选购 BNC 对双“球”式保护夹导线 (3787C36)



TECHNICAL ASSOCIATES Divisions of  **OVERHOFF TECHNOLOGY**

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

tagold@nwc.net

WWW.TECH-ASSOCIATES.COM