

ANALYZING RATEMETER SCALER

分析计数仪

PORTABLE

便携式

Model - LAM-SCA

FEATURES:特点

- VERSATILE AC OR RECHARGEABLE BATTERY
- 通用 AC 供电或充电电池
- THREE SINGLE CHANNEL ANALYZER WINDOWS
- 三个独立通道分析窗
- SWITCH SELECTABLE
- 开关选择
- SIX DECADES
- 6 数量级
- CRYSTAL CONTROLLED
- 晶体控制
- USE WITH ANY T/A GM, PROPORTIONAL, OR SCINTILLATION ALPHA, BETA, GAMMA, X-RAY NEUTRON PROBE
- 同任何 TA 公司 GM, 正比或闪烁 α β γ x-ray 中子探头使用
- SPLASH PROOF
- 防溅



DESCRIPTION: 描述

The **LAM-SCA** is a sturdy portable instrument designed for rugged field use.

LAM-SCA是一款结实便携仪器设计可用于野外

- Both integrate and rate-meter functions.
- 总计数及计数率功能
- Single channel analyzer with three presettable windows.
- 单道分析仪带三个预设窗
- Variable high voltage 0-2000v.
- 可变化高压0-2000v



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303

818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP

ANALYZING RATEMETER SCALER

分析计数器

PORTABLE

便携式

Model - LAM-SCA

- All calibration pots are available from outside the case.
- 所有刻度分压计可箱外设定
- All closures are gasket sealed to result in a splashproof instrument.
- 所有接口处垫圈密封所以防溅
- LCD style scaler readout.
- LCD 读数器

The time base for integrate operation is user settable. The LAM-SCA accommodates pulses from all types of detectors including scintillators, proportional and GM detectors. Six digits are incorporated into the ratemeter. 总计数时基用户设定，LAM-SCA适合各种探测器脉冲分析，包括闪烁体，正比和GM探头。六位数读数器

Gate times for the integrate mode may be set from 1 to 10,000 seconds. The integrate capability is particularly useful for increasing the accuracy of rate measurements and for operating optional printer.

总计数模式控制时间可设定范围1-10,000秒，整合能力对增加计数率测量精度和打印机操作尤其有用。

Power switch and HV pot and other controls are designed to prevent inadvertent change. The output of the high level alarm is controlled by a volume mute switch.

电源开关和高压电位计及其它控制设计防止疏忽操作，高限报警由音量开关控制。

Standard features include jack for AC adapter and serial output jack with optional USB adaptor. Yet the overall instrument, including all of these functions and battery life up to 1 week, weighs only 5 pounds.

标准配置包括AC适配器，串口输出，可选USB适配器。整个仪器包括所有功能和寿命长达1周电池总重才5磅。

SPECIFICATIONS:

规格

- **Digital Readout:** 6 digit LCD Rate, 8 digit integrate.
- **数字读出器:** 6位LCD计数率，8位数总计数
- **Time Base:** Crystal controlled 1-10,000 seconds, user settable.
- **时基:** 晶体控制1-10,000秒，用户设定
- **Display Modes:** Rate, Integrate.
- **显示模式:** 计数率，总计数
- **Range:** 量程
Usable Probes Cover Range: 1uR/hr to 1000 R/hr; 0 to 30,000 Cps; 0.1 mRem/hr to 10 Rem/hr.
可用探头覆盖量程:



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303

818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP

ANALYZING RATEMETER SCALER

分析计数器

PORTABLE

便携式

Model - LAM-SCA

- **Audio Alarm:** Piezo electric sounder with volume control.
- **声音报警:** 压电音带音量控制
- **Single Channel:** 单量程
- **3 Switch Selectable Windows:** 3开关选择窗
2 preset (resettable) window positions plus one "variable".
2个预设窗位置加一个“可变”窗位置
- **Analyzer/Discriminator:** 10-turn, 1000 division pot for each threshold.
10-turn, 1000 division pot for window width.
分析仪/甄别器: 10转, 每个阈值1000刻度电位计
10转, 每个窗宽1000刻度电位计
- **Detector:** 探头
Mates with T/A Probes, any GM, Proportional or Scintillation:
与TA公司探头兼容, GM, 正比或闪烁探头
Alpha, Beta, Gamma, Positron, X-Ray, Neutron, Tritium.
 α β γ 正电子, X-Ray, 中子和氚
- **Detector Connector:** BNC bulkhead mount (MHV optional).
- **探测器连接件:** BNC夹板式连接件 (可选MHV)
- **Detector Bias:** 0-2000V regulated and filtered.
- **探头偏压:** 0-2000V 调节过滤
- **Supply:** High Voltage is adjustable with the 10 turn dial.
- **电压:** 可调节高压带10转
- **Settable scale factors allow readout in almost any units.**
- **可设定定标系数允许读出任何单位**
- **Engineering Units:** User can input correct conversion factor and change to any units.
- **单位:** 用户可输入正确转换因子转换成任何单位
- **Controls:** Front Panel: On-Off, Alarm-mute, Rate, Integrate, Reset.
- **控制:** 前板: 开-关, 报警-静音, 计数率, 综合计数, 重设
- **Calibration:** Digital input of calibration factor gives high precision adjustment.
- **校准:** 校准系数数字输入给出高精度调整
- **Alarm:** 2000 Hz audio tone with audio "mute" switch + RED LIGHT, high current relay.
- **报警:** 2000 Hz 音调带静音旋钮+红灯, 大电流继电器
- **Serial Output:** Two way, RS-232 standard, USB optional.
- **串口输出:** 两路标准RS-232, 可选USB



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net
WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP

ANALYZING RATEMETER SCALER

分析计数器

PORTABLE

便携式

Model - LAM-SCA

- **Construction:** NEMA-4X gasketed polycarbonate case with handle:
Rugged / splash-proof.
All plug in circuit cards.
结构: NEMA-4X密封PC外箱, 带把手。结实防溅, 插板式电路
- **Available Options Include:** 可提供包括:
 - **Computer interface:** RS-232, USB, etc. or complete data logging and acquisition systems.
Output for Digital Printer
电脑接口: RS-232, USB等, 或全数据录入系统, 数字打印机输出

POWER:

电源

- **Power:** 105-125 volts, 50-60 Hz (220 V optional)
- **电源:**
- **Batteries:** 12v, 4.8 Amp Hour built-in Li-ion battery pack with AC Charger Adapter
- **电池:** 12V, 4.8安培小时, 内置锂电池组带AC充电器适配器。
- **Battery Life:** 3-5 days at 8 Hour/day
- **电池寿命:** 每天8小时, 3-5天

WEIGHT AND DIMENSIONS:

重量

- **Dimensions:** 25cm L x 10.5cm W x 18cm (10" x 4.1" x 7").
Includes handle
尺寸: 包括把手25cm长 x 10.5cm宽 x 18cm
- **Weight:** 2.5kg (5lbs) including batteries.
- **重量:** 包括电池2.5千克
- **Shipping Weight:** 4kg (8lbs)
- **邮寄重量:** 4千克
- **Options:** Connection for interface to printer or computer
SI units
Printer
选择: 打印机或电脑接口, SI单位, 打印机

Over 50 Different T/A Probes And Sample Counter Detectors:



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net
WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP

ANALYZING RATEMETER SCALER

分析计数器

PORTABLE

便携式

Model - LAM-SCA

超过50中不同TA公司探头和样品计数探头:

Probe holder supplied - no charge if probe and PRS-5 purchased together

提供探头托-如果同时与PRS-5购买免费

TA Detector Model Numbers

TA探头型号

A	P6-LB	F	DMU-1000
B	PAS-9	G	P-15
C	BGS-IN	H	STB-TF-6
D	COLLIMATOR	I	TS-26
E	PLS-04	J	PN-3



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303

818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP

ANALYZING RATEMETER SCALER

分析计数器

PORTABLE

便携式

Model - LAM-SCA

RANGE SPECIFICATIONS: 量程规格

Choose Any Probe Below or Any TA or Compatible Probe.

选择任何以下探头偶然任何 TA 公司或其它兼容探头

PROBE 探头	DESCRIPTION 描述	RANGE 范围						UNITS 单位
ALL PROBES	ALL PROBES	0.1	1	10	100	1,000	10,000	cps
GM	Thin window Alpha-Beta, Gamma, X-ray 薄窗 α β γ x-线							
P-15	2" dia Pancake 直径 2" 扁平管		.02	.2	2	20	200	mR/h
P6-LB	Low Background 低本底		.1	1	10	100	1,000	mR/h
SCINTILLATION 闪烁体	SCINTILLATION 闪烁体							
PGS-3T	Low Energy Gamma 低能伽马			.01	.1	1	10	mR/h
PGS-3I	Low / Mid Energy Gamma 低/中能量伽马			.03	.3	3	30	mR/h
BGS-2505	Low Energy BGO Probe 低能 BGO 探头			.01	.1	1	10	mR/h



TECHNCIAL ASSOCIATES

7051 Eton Ave., Canoga Park, CA 91303

818-883-7043 (Phone) 818-883-6103 (Fax) tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

A Division of



US NUCLEAR CORP