

PIPE/GROUND MONITOR SYSTEM

Model # PGM-2L

FEATURES:

- SMALL DIAMETER
- HIGH SENSITIVITY
- RUGGED
- MOISTURE RESISTANT
- OPTIONALLY SUBMERSIBLE
- PORTABLE

DESCRIPTION: The PGM-2L is truly a **lightweight portable** monitoring system which consists of a moisture resistant BGO* scintillation probe 5/8" in diameter and up to a 40 foot cable. The readout for this system is a Model PRS-5 Ratemeter/Scaler which includes three single channel switch selectable analyzers. The ten inch long probe contains a sensitive/rugged photo-multiplier, dynode resistor string, and a 1/2" x 2" BGO scintillation crystal.

APPLICATION: This system is extremely useful for location or movement of underground radioactivity by use of pipes driven into the formation.



Figure 1: PGM-2L

SPECIFICATIONS:

READOUT: See PRS-5 Data Sheet

PROBE

Length: 10"

Weight: 10 oz.

Diameter: 5/8"

Scintillator Type: BGO*

Scintillator Size: 1/2" x 2"

Drive Capability: 40' into PRS-5 Readout Package

Sensitivity: Typically 350,000 cpm/mR/hr

Efficiency: Better than 50% for Cs¹³⁷ gammas

***High Density:** 7.13 (vs. 3.67 for NaI) nearly doubles sensitivity for gammas in general. High atomic # enhances sensitivity to low energy gammas by a further factor of up to 10.

****Options:** Immersion proof probe

TA

TECHNICAL ASSOCIATES

7051 ETON AVENUE * CANOGA PARK, CA 91303 TELEPHONE (818) 883-7043 * FAX(818) 883-6103

\$Revision: 1.2 \$