

DIGITAL FRISKER

Model ~ TBM-15-D

FEATURES:

- ALPHA, BETA AND GAMMA
- LIGHTWEIGHT
- ONE HAND OPERATION (PROBE HOLDER)
- NO RANGE SWITCHING
- DETACHABLE PANCAKE PROBE
- BUILT-IN SONALERT
- ANTI-SATURATION CIRCUIT
- OPTIONAL: USB PORT
- **IP64**
- **CE Mark**



DESCRIPTION:

- Small Digital Ratemeter with separable 2" diameter pancake probe.
- Alpha, Beta and Gamma detection.
- Reads out in mR/hr (Optional μ Sv/h or cpm, cps).
- Thin probe window is recessed and protected by sturdy stainless steel grill.
- Anti-saturation circuit will not fall below full scale in high fields.
- Tested to 100 R/hr.
- Sonalert gives audible rate indication.

APPLICATION:

Its small size, light weight, separable probe and large detector area make this a very useful monitor for surveying bench tops or checking hands, clothes and fingertips for almost any radioactive contamination.



TECHNICAL ASSOCIATES

Divisions of



US NUCLEAR CORP

OVERHOFF TECHNOLOGY

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

Ticker UCLE

DIGITAL FRISKER

Model ~ TBM-15-D

SPECIFICATIONS:

Read-out:	Rugged 6 digit display.
Ranges:	0.01 to 200 mR/hr, no range switching. (0-500,000 cpm)
Linearity:	+/- 15% of full scale with pulse generator.
Battery Test:	Push button.
Audio:	Sonalert.
Two Time Constants:	Fast & Slow (each is user programmable) 0 to 90% of final reading. User Settable: 2 sec to 99 seconds.
Detector:	
Type:	T-1190 2" diameter (5cm) ``pancake GM" tube.
Plateaus:	150V <10% / 100V
Window Diameter:	1 3/4"; 4.5 cm. Area 16 cm ²
Window Thickness:	1.5 mg/cm ²
Dead Time:	70 μ sec Max
Quench Gas:	Halogen for long life.
Background:	Typical 50 cpm. Thin profile of tube (13mm) gives low background.
Efficiency:	100% for all Betas & Alphas with sufficient energy to penetrate thin window.
Temperature:	-10°C to +50°C with high quality batteries.
Calibration:	Single master calibration pot and programmable calibration factor.
Beta Efficiency:	C-14 > 6%, Sr-90/Y-90 > 25% 4 pi.
Speaker:	Built-in Audible Click for detector pulse, on-off Volume switch on panel.
Pulse-count:	Green LED.
Alarm:	Settable over entire instrument range.
Warning:	Red LED.
Power:	6 ``AA" cells.
Battery Life:	100 hours in normal operation (Greater with Li or NiMH Battery).

WEIGHT & DIMENSIONS:

Dimensions:	3" w (7.6 cm) x 5 1/4" long (13.3 cm) x 2 1/2" high (6 cm) (excluding probe and handle).
Weight:	
Electronics Only:	22 oz. (625 gm).
Total Weight:	Including separable pancake probe 34oz. (0.97 kg).

OPTION: Serial Port: Allows real time data logging to portable PC.



TECHNICAL ASSOCIATES

Divisions of



US NUCLEAR CORP

OVERHOFF TECHNOLOGY

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

tagold@nwc.net

WWW.TECH-ASSOCIATES.COM

Ticker UCLE